

# access

L I G H T I N G

## INSTALLATION INSTRUCTIONS

### IMPORTANT

Before assembling your access lighting fixture, please make sure that you carefully read through these instruction sheets. Consider having your fixture installed by a qualified licensed electrician.


**NOTE:** The important safeguards and instructions that appear in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that can't be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

### GENERAL INFORMATION

All electrical connections must be in accordance with all ordinances, Local and National Electrical Codes. These fixtures are intended for mounting to a standard 4" x 2 1/2" metal octagon outlet box. The box must be directly supported by the building structure and U.L. Recognized.

### STEP BY STEP INSTRUCTIONS

Before starting your installation disconnect the Power by turning off the Circuit Breaker or by removing the fuse at the fuse box. Just turning the light off at the light switch is not sufficient to prevent electrical shock.



**COLLECTION**  
AERIA

**APPLICATION**  
Pendant

**MODEL NO.**  
52077

### WHAT WE PROVIDE

- Mounting Hardware
- Crossbar Plate
- 7 x Glass + mesh shade
- 7 x 20W G4


### WHAT YOU NEED

- Screwdriver
- Wire Cutters
- Wiring Supplies as Specified by Electrical Code

1

### PREPARE FIXTURE AND MOUNT THE CROSSBAR


If there is an existing fixture remove it.  
Expose the supply wire from the outlet box.  
Mount the crossbar to the junction box with the supplied screws



2

## MAKE WIRE CONNECTIONS


Gently pull the supply wires through the hole in the crossbar. Connect the black supply wire to the black fixture wire. Secure with the supplied wire nuts. Connect the white supply wires to the white fixture wire. Secure with the supplied wire nuts. Either wrap the green wire around one of the protruding screws or connect it to the supply ground wire. Secure all wire with electrical tape (not supplied). Tuck all wires carefully into the J-Box.



3

## MOUNT FIXTURE TO THE CROSSBAR PLATE


Fix the fixture canopy up to the crossbar. Align the holes in the sides of the crossbar with the designated holes in the canopy. Secure with the supplied screws.



4

## INSERT THE BULBS

Insert the supplied bulbs.  
 MAXIMUM WATTAGE 20W.  
 DO NOT EXCEED THE WATTAGE AS STATED  
 ON THE WARNING LABEL AND IN THE INSTRUCTION  
 SHEETS



5

**SECURE THE GLASS AND MESH SHADE**

Insert the parts over the socket by sequence as follow: cap of socket, washer, glass shade, washer and secure the mesh by screwing onto the threads on the socket.



6

**RESTORE THE ELECTRICITY AND CHECK THE OPERATION OF YOUR NEW ACCESS FIXTURE**

