


# Assembly Instruction Sheet #S-9962C18 For Style 9962C18

Tools Required: Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.  
 Light Source: (4) E26 MAX 60W (Not Included).  
 Estimated Assembly Time: 10-20 minutes.  
 Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.


**⚠Warnings and Cautions**  
 Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

**Package Contents**

**STEP 1 - Combination Metal Frame**




**STEP 2 - Release Crossbar from Ceiling Canopy.**




Hardware Contents		
PART	DESCRIPTION	QUANTITY
BB	Wire Nut	2pcs
CC	Outlet Box Screw	2pcs

**STEP 3 - Attach Crossbar to Outlet Box.**




**STEP 5 - Install Bulbs.**



**STEP 4 - Wire Connections**  
 A. Use standard wire connectors (not included) to make all wire connections. Twist connectors until wires are tightly joined together. Wrap each connection with approved electrical tape and carefully stuff all the connected wires into the Outlet Box.

White wire from outlet box connects to White wire from fixture.  
 Black wire from outlet box (or Red) connects to Black wire from fixture.  
 Bare, or Green Ground wire from outlet box connects to Ground wire from fixture.  
 Bare, or Green Ground wire from fixture connects to Green Ground Screw on the Crossbar.



**STEP 6 - Install Metal Frame to the Fixture Body.**

