

Florestone Saflor® Corner Shower Receptors

Architect's Specifications

Furnish and install Saflor® Shower Receptor manufactured by Florestone Products Co. (Model Number - see table)
The receptor shall be furnished with a slip-resistant design that does not interfere with the flow of water nor trap it. Receptor to have integral molded drain and sill with aluminum cap on the side adjacent to the threshold. Receptor to have not less than 1" flange on remaining sides. Receptor to be stain and fungus resistant. Color to be off-white and will be resistant to fading and abrasion. Model shall conform to ANSI-Z-124.2.

SAFLOR® Options and Accessories

Josam Jiffy-Joint™

Wedge-Lok® Seal

Strainer, Brass


Strainer, Chrome

Strainer, Plastic

Repair Kit




One piece, right or left-hand corner model with metal capped sill 3/4" wide and 1 1/4" high for glass side wall installation on left or right side of threshold.




SPECIFY RIGHT OR LEFT-HAND SILL.

CORNER



Right Hand



Left Hand

Model	A	B	C	D	E	WT.
3232-2	33 3/8"	32"	16"	17 3/8"	16"	50
3434-2	35 3/8"	34"	17"	18 3/8"	17"	54
4234-2	43 3/8"	34"	21"	22 3/8"	17"	64
4832-2	49 3/8"	32"	24"	25 3/8"	16"	70
4834-2	49 3/8"	34"	24"	25 3/8"	17"	75
5434-2	55 3/8"	34"	27"	28 3/8"	17"	84
6032-2	61 3/8"	32"	30"	31 3/8"	16"	86
6034-2	61 3/8"	34"	30"	31 3/8"	17"	96

**Dimensions subject to change without notice.
Contact Florestone Products to verify product specifications.**



FLORESTONE PRODUCTS CO., INC.

2851 Falcon Drive • Madera, CA 93637

T. 559.661.4171 • T. 800.446.8827

F. 559.661.2070 • florestone.com

Standards:

I.A.P.M.O. International Association of Plumbing and Mechanical Officials
File No. 0687.

ANSI American National Standards Institute - Specifications Z-124.2.

HUD/FHA National Specifications UN-73.

