

13306

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

1. Attach the mounting bar (6) with mounting screw (7) to the outlet box (1).
2. Connect the stems (19) (18) (17) (depending on desired height). Attach them to the nipple on the top of the fixture (20).
3. Open quick link (15) and attach it to fixture loop (16) and canopy loop (12), then close quick link (15).
4. Carefully feed the fixture wires through the quick link (15), canopy loop (12), canopy (11) and nipple assembly.
5. With a drill, make a hole near outlet box (1) and insert a plastic anchor (21). With the help of a friend, lift the fixture.
6. Attach washer (23) and support cable (22) from canopy (11) onto the anchor (21) by using wood screw (24). Secure tightly.
7. Pull out the outlet wire and ground wire from the outlet box, make wire connections with wire nut (6) as follow:
 - Connect the smooth-coated wire (marking) or Black wire from fixture to the Black wire (3) from power source.
 - Connect the ribbed-coated wire (w/o marking) or White wire from fixture to the White wire (2) from power source.

- Attach the fixture ground wire to mounting bar (6) with the ground screw (8). Connect it to the house ground wire (4) with the wire nut (5).
9. Place canopy (11) against the ceiling, ensuring nipple (10) is protruding through the hole in canopy (11). Secure the fixture in place to nipple (10) with nut (13) and ball nut (14).
 10. Install bulbs: (bulbs not included)
(Don't exceed the maximum capacity recommended on the sockets).

INSTALLATION IS NOW COMPLETED

