

roject:	
ixture Type:	
ocation:	
ontact:	

Wall mounted . Damp location listed PROGRESS LED

Description:

The Miter LED 24in linear bath bar highlights a beautiful layered effect to enhance a variety of interior areas. Each clear beveled glass panel is hand cut and positioned together, creating visual interest that extend to the corners. To complete the form, a back plate and linear accents frame the glass in a Brushed Nickel finish. Can be displayed horizontally or vertically. An integrated LED source provides a variety of energy and cost savings benefits.

Specifications:

- Brushed Nickel (-009) (plated)
- Steel Construction
- Clear glass Beveled Panel, White glass diffuser
- · The clear beveled glass panel is in front of a cased white mitered glass shade
- · Linear accents frame the beveled glass
- · The LED light is diffused to create an even glow
- · The backplate and straps are finished in Brushed Nickel
- · Its fashion-forward style complements Modern and Traditional interiors
- Mount horizontally or vertically on the wall in bath and vanity settings to enhance a spa-like atmo-
- Measures 24in W x 5in ht.
- 36w integrated LED, 1,675 delivered lumens 54 lumens/watt, 3000K color temperature, 90+ CRI.
- · ETL Safety listed for use in damp locations
- · Progress Lighting products are designed for exceptional quality, reliability, and functionality
- · Includes installation instructions and mounting hardware
- Coordinating fixtures available
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting back plate for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" ADA

For more information visit our website: www.progresslighting.com

Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	36w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1975/54 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Warranty	5 year limited warranty
Labels	cETLus Damp location listed
	Meets California Title 24 JA8-2016



Images:



Dimensions:

Width: 24" Depth: 3-7/8" Height: 5"

H/CTR: 2-1/2313" (mounted horizontal)

Glass

Width: 24-1/16" Height: 4-5/8"



Wall mounted • Damp location listed PROGRESS LED

P300152-009-30

Dimming Notes:

is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron - NTELV-300
Lutron - DVELV-300P
Lutron - Caseta Wireless
Leviton - 6672
Leviton - 6674
Lutron - AYCL-153P
Lutron - AYLV-600P
Lutron - MAELV-601
Leviton - AWRMG-EAW
Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.