

PSH Plus Technical Specifications

Technical Data

Certified to ANSI/UL Std. 174
Conforms to CAN/CSA Std. 22.2 No. 110

ISO 9001
CERTIFIED



Tested and certified by WQA against
NSF/ANSI 372 for lead free compliance

Model	PSH 20 Plus	PSH 30 Plus
Catalog #	235968	235969
Nominal water volume	21 gal / 80 l	32 gal / 120 l
Amount of mixed water 104°F / 40°C	37 gal / 139 l	58 gal / 221 l
Maximum flow rate	6.2 gpm / 23.5 l/m	6.2 gpm / 23.5 l/m
Phase Single - 60/50 Hz	1	1
Voltage	240 V	240 V
Amperage draw	13.1 A	13.1 A
Recommended breaker	20 A	20 A
Heating element	3.0 kW	3.0 kW
Standby energy consumption / 24 h @ 149°F / 65°C	2487 Btu / 0.729 kWh	3661 Btu / 1.073 kWh
First Hour Rating	30 gal. / 113.6 l	28.03 gal. / 106.1 l
Temperature Range	86-167 °F / 30-75 °C	86-167 °F / 30-75 °C
Diameter	20" / 510 mm	20" / 510 mm
Depth (with mounting bracket)	20 ¹ / ₂ " / 520 mm	20 ¹ / ₂ " / 520 mm
Height	36 ¹ / ₄ " / 922 mm	48 ³ / ₈ " / 1229 mm
Weight (without water)	62.2 lbs / 28.2 kg	86.2 lbs / 39.1 kg
Weight (with water)	238.5 lbs / 108.2 kg	350.8 lbs / 159.1 kg